



NOBLES[®]
ENGINEERED BY TENNANT COMPANY

SPEED SCRUB[®]
Built to be **tough**. Made to be **easy**.



Reliable, effective cleaning results. Anytime. Every time.

The Speed Scrub®

It's rugged.

From non-corroding cast aluminum scrub decks & squeegee frames, to over 100,000 real-world vacuum testing cycles, the Speed Scrub is built to withstand daily wear and tear.

It's easy.

Spend less time training and maintaining, and more time cleaning with simple one-button Quick-Train™ controls and easy, no-tool squeegee replacement.

It performs.

Floors are immediately dry with optional FaST™ technology. Combine that with 100% water recovery – even in 180-degree turns – and noise-levels as low as 67 dBA, and this is the anytime scrubbing machine.



Five no-nonsense features

1. Powerful motors

Get a reliable clean from two 0.75 hp brush motors that deliver vigorous agitation, while the 0.85 hp vacuum system is pulling 62 in / 55 mm of waterlift.



2. Low noise level

Made to be used in the quietest places, the Speed Scrub has an extremely low noise level – as low as 67 dBA.



3. On-board charger

No need to worry about where to charge the machine. Just find any 120 volt outlet, plug it in, and you're good to go.



FaST: The Safe Scrubbing Alternative® Tested and certified for results.



FaST stands for Foam-Activated Scrubbing Technology. And it's been certified "high-traction" by the National Floor Safety Institute - which means, when cleaning with FaST, floors have a higher traction, reducing the risk of slip-and-fall. It's also been

tested safe for floor finishes by ASPEN, the national independent testing lab.

With FaST technology you get...

No chemical residue, no chemical handling, and less waste.

Best of all, with FaST you get up to 150 minutes of non-stop, productive scrubbing from fewer empty/fill cycles - 90% longer than the closest competitive scrubber.



4. Quick and easy brush/squeegee replacement

No tools are needed - EVER - to replace brushes or blades, and operators can stop worrying and messing with squeegee adjustments, it's factory set.



5. Iron-clad warranty

3 years, 2500 hours on parts and labor (excluding batteries).
10 years on tanks.





Engineered by Tennant Company, the Speed Scrub is manufactured by the best – making it a smart, reliable choice for your no-nonsense cleaning needs.

Optional Equipment

FaST, off-aisle wand, E-stop, gel batteries

Brushes & Pads Available

Scrubbing brushes – non-scuff polypropylene, soft nylon, abrasive bristle.

Scrubbing pads – stripper pad (brown), scrubber pad (blue), buffing pad (red), polishing pad (white).

Warranty

3 years/2500 hours on parts and labor (excluding batteries).
10 years on rotationally-molded polyethylene tanks.

Nobles

701 North Lilac Drive
P.O. Box 1452
Minneapolis, MN 55440-1452
800.553.8033
763.540.1200
f: 763.513.2112
www.nobles.com
nobles@tennantco.com

Features	Disk	Cylindrical
Cleaning path	24 in / 600 mm 28 in / 700 mm 32 in / 800 mm	26 in / 650 mm 32 in / 800 mm
Solution tank capacity	22.5 gal / 85 L	22.5 gal / 85 L
Productivity (per hour) Theoretical max	(24") 26,400 ft ² / 2,500 m ² (28") 30,800 ft ² / 2,900 m ² (32") 35,200 ft ² / 3,300 m ²	(26") 28,600 ft ² / 2,700 m ² (32") 35,200 ft ² / 3,300 m ²
Estimated coverage* (conventional)	(24") 17,875 ft ² / 1,660 m ² (28") 20,800 ft ² / 1,900 m ² (32") 24,000 ft ² / 2,200 m ²	(26") 19,200 ft ² / 1,790 m ² (32") 24,000 ft ² / 2,200 m ²
Estimated coverage* (FaST)	(24") 20,750 ft ² / 1,900 m ² (28") 22,750 ft ² / 2,100 m ² (32") 26,250 ft ² / 2,400 m ²	(26") 21,000 ft ² / 2,000 m ² (32") 26,250 ft ² / 2,400 m ²
Solution flow rates Conventional (fully variable) FaST	0-0.5 gpm / 0-1.89 lpm (24") 0.15 gpm / 0.57 lpm (28 & 32") 0.22 gpm / 0.83 lpm	0-0.6 gpm / 0-2.27 lpm (26") 0.15 gpm / 0.57 lpm (32") 0.22 gpm / 0.83 lpm
Scrub motors	(2) 0.75 hp / 0.56 kW	(2) 0.63 hp / 0.47 kW
Scrub motor speed	220 rpm	1500 rpm
Brush/pad down pressure	Up to 120 lb / 54 kg	Up to 120 lb / 54 kg
Recovery tank capacity (includes demisting chamber)	27 gal / 102 L	27 gal / 102 L
Vacuum fan Motor Stages Water lift	0.85 hp / 0.640 kW 3-stage 62 in / 1,570 mm	0.85 hp / 0.640 kW 3-stage 62 in / 1,570 mm
Propel speed (variable to) Transport Scrubbing	2.7 mph / 4.3 km/h 2.5 mph / 4.0 km/h	2.7 mph / 4.3 km/h 2.5 mph / 4.0 km/h
Batteries (24 V system, charger included) Standard run time** Optional sealed (AGM) run time**	(4) 6 V, 235 AH / up to 5 hrs (4) 6 V, 200 AH / up to 4 hrs	(4) 6 V, 235 AH / up to 5 hrs (4) 6 V, 200 AH / up to 4 hrs
Gradeability (ramp climb) Scrubbing/transporting (full) Trailer ramps (empty)	3.0° / 5.0° 11°	3.0° / 5.0° 11°
Product length	(24") 53 in / 1,350 mm (28") 55.5 in / 1,410 mm (32") 58 in / 1,470 mm	55 in / 1,400 mm
Product width (scrub head)	(24") 25.4 in / 640 mm (28") 29 in / 740 mm (32") 33 in / 840 mm	(26") 28 in / 710 mm (32") 34 in / 860 mm
Squeegee width	(24") 35.7 in / 910 mm (28") 41.3 in / 1,050 mm (32") 46.6 in / 1,180 mm	(26") 41.3 in / 1,050 mm (32") 46.6 in / 1,180 mm
Product height	44 in / 1,120 mm	44 in / 1,120 mm
Product weight (with batteries)	(24") 569 lb / 258 kg (28") 593 lb / 269 kg (32") 606 lb / 275 kg	(26") 606 lb / 275 kg (32") 615 lb / 279 kg
Sound level*** (operator's ear)	67 dBA	68 dBA

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.
** Run times are based on Continuous Scrubbing Run Times.
*** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA.